

=====
* LMS Version 3.61 Date=Jul 23,1996 Time=Tue 3:12PM
=====
* Speaker Parameter Measurement Data (SPM)
=====

Method: Single Impedance Curve

Free Air Curve Num= 10 Name=~~Z~~ZPT25

ZPT 25

----- Electrical/Mechanical Parameters -----
Revc(DC VC Res) = 4.5600 Ohm Qms (Mech Q) = 1.0554
Fo (Res Freq) =1373.9990 Hz Qes (Elec Q) = 1.2858
Zo (Zmax at Fo) = 8.3027 Ohm Qts (Total Q) = 0.5796

----- Motor Impedance Parameters -----
Levc (Induc at 1kHz) = 0.0000 mH Rem(Res at 1kHz)= 0.0000 Ohm
Levc (Induc at 20kHz) = 0.0000 mH Rem(Res at 20kHz)= 0.0000 Ohm
Krm (Resistance Cons)= 0.0000 mOhm Erm(Resis Expont)= 0.0000
Kxm (Reactance Cons)= 0.0000 mH Exm(React Expont)= 0.0000

=====
Pmax: 50W CONTINUOUS ~~70~~ WATT PEAK
SENS: 90dB
MOUNTING DIAMETER 2.1" FLUSH
=====